


 $R\T$ ownship 138\Range 80\Replat Metro Ind Park\LOT 1 BK 2.dwg, PLAN, 4/14/2014 11:01:33 AM,

- WATER SERVICE LINE SHALL BE CLASS 200 POLY. PROVIDE A CURB VALVE AND BOX MEETING RURAL WATER STANDARDS. ADJUST THE BOX TO 1" ABOVE FINISHED GRADE.
- COORDINATE LOCATION AND ELEVATION OF THE WATER AND SEWER CONNECTION LOCATIONS AT
- PERFORM GRADING TO THE ELEVATIONS SHOWN. THOUROUGHLY COMPACT AND MOISTURE CONDITION THE AREAS TO RECEIVE GRAVEL. PERFORM GRAVELING TO A 4" COMPACTED THICKNESS USING CLASS 5 ROAD GRAVEL OR OTHER OWNER ACCEPTED MATERIAL.
- 4. SEPTIC SYSTEM DESIGNED FOR 1 SINK, 1 TOILET.


SYM.	COMMON NAME	SCIENTIFIC NAME	SIZE	QNTY.
SM	SILVER MAPLE	Acer saccharinum	2" Cal.	7



PROTECT THE IMPROVEMENTS ON SITE AND ON THE ADJOINING PROPERTIES. PROVIDE BARRICADES, COVERINGS OR OTHER TYPE OF PROTECTION AS NECESSARY TO PREVENT DAMAGE AND TO SAFEGUARD AGAINST INJURY TO EXISTING


ALL LANDSCAPE PLANTINGS ARE TO BE WATERED BY THE LANDSCAPE CONTRACTOR THE SAME DAY THAT THE PLANTING OCCURS. THE OWNER WILL BE RESPONSIBLE FOR PROVIDING WATER FOR THIS TASK. IF WATER IS NOT AVAILABLE AT THE BUILDING, THE LANDSCAPE CONTRACTOR SHALL PROVIDE ALTERNATIVE METHODS FOR WATERING. SOLITARY TREES DO NOT NEED TO BE EDGED AROUND, HOWEVER ORGANIC WOOD MULCH SHALL BE PLACED AROUND THE ALL PORTIONS OF THE SITE THAT IS DISTURBED BY CONSTRUCTION SHALL BE COVERED WITH A MINIMUM OF 6" OF TOPSOIL AND SEEDED AS SOON AS PRACTICAL TO MINIMIZE WIND AND WATER EROSION. ALL IMPORTED TOPSOIL SHALL BE NATURAL, FRIABLE, FERTILE, FINE, SANDY-LOAM TOPSOIL. IT SHALL BE FREE FROM SUBSOIL, NOXIOUS WEEDS, STONES, LIME, CEMENT, ASHES, SLAG, OR OTHER DELETERIOUS MATTER.

LEGEND EXISTING ITEMS



CONTOUR

PROPOSED LEGEND



Copyright © 2014 by Swenson, Hagen & Co. All rights reserved. No part of this drawing may be used or reproduced in any form or by any means without the express written permission of Swenson Hagen & Co.

The locations of existing underground utilities are shown in an approximate way only and have not been independently verified by the owner or its representative. The contractor shall determine the exact location of all existing utilities before commencing work, and agrees to be fully responsible for any and all damages which might be occasioned by the contractor's failure to exactly locate and preserve any and all underground utilities.

DRAWN BY: . CHECK BY: MJB DATE: <u>3/28/2014</u> FILE DESC: 138-80 METRO INDUS PARK COMPUTER FILE: LOT 1 BK 2 SURVEY FILE:

MARCH 28, 2014

NORTH DAKOTA

UTILITIES UNDERGROUND LOCATION SERVICE

1-800-795-0555